



• Installation Details

Refer to the Crisp handling and installation guide for in-depth instructions.

Please add an overage of 12-15%. This allows for greater flexibility during the evaluation process on-site to ensure the best outcome.

• Finish Specifications

All products are factory-finished and arrive on-site ready for installation

• Pre-finish: Crisp Hemlock features a two-coat system.

- First conditioning, clear coat is applied to front face, back and two edges.

- The second is a color coat that is applied to the front-finished face.

• Applied Finish: Broda Clarity Acrylic, Water-borne, low V.O.C, film-building finish

• Color: Broda Clarity 255 Fog

• Coating Options:

- Broda Clarity acrylic clear top coat, available in gloss, satin or flat finish.

• Species

Western Hemlock is a medium-to-large-sized, evergreen conifer. Perfect for wood panelling, it boasts beauty, strength, and versatility. Sourced from sustainably managed forests, Hemlock's durability and decay-resistant nature ensure long-lasting wood products. With its fine texture and light color, it's ideal for staining, offering a personalized, elegant finish which blends seamlessly with any architectural style

• Wood Grade

Crisp Hemlock is available in:

- C&BTR clear vertical grain 3'-20' random tally

Product pictures of Hemlock on crisp wood co website features clear vertical grain unless noted

• Moisture Content

Crisp Hemlock is kiln-dried to a MC of 12-15%. This may fluctuate during transportation or warehousing.

Make sure to acclimatize on-site before installation.

• Surface and Texture

Crisp Hemlock smooth is pre-sanded to a smooth finish.

Crisp Hemlock can be installed vertically or horizontally.

• Profiles & Dimensions

The profiles shown are standard dimensions. Crisp can supply any custom profile

