



**• Installation Details**

Refer to the Crisp handling and installation guide for in-depth instructions.

Please add an overage of 12-15%. This allows for greater flexibility during the evaluation process on-site to ensure the best outcome.

**• Finish Specifications**

All products are factory-finished and arrive on-site ready for installation

**• Pre-finish:** Crisp Hemlock features a two-coat system.

- First conditioning, clear coat is applied to front face, back and two edges.

- The second is a color coat that is applied to the front-finished face.

**• Applied Finish:** Broda Clarity Acrylic, Water-borne, low V.O.C, film-building finish

**• Color:** Broda Clarity 242 Granville

**• Coating Options:**

- Broda Clarity acrylic clear top coat, available in gloss, satin or flat finish.

**• Species**

Western Hemlock is a medium-to-large-sized, evergreen conifer. Perfect for wood panelling, it boasts beauty, strength, and versatility. Sourced from sustainably managed forests, Hemlock's durability and decay-resistant nature ensure long-lasting wood products. With its fine texture and light color, it's ideal for staining, offering a personalized, elegant finish which blends seamlessly with any architectural style

**• Wood Grade**

Crisp Hemlock is available in:

- C&BTR clear vertical grain 3'-20' random tally

\*Product pictures of Hemlock on crisp wood co website features clear vertical grain unless noted\*

**• Moisture Content**

Crisp Hemlock is kiln-dried to a MC of 12-15%. This may fluctuate during transportation or warehousing.

Make sure to acclimatize on-site before installation.

**• Surface and Texture**

Crisp Hemlock smooth is pre-sanded to a smooth finish.

Crisp Hemlock can be installed vertically or horizontally.

**• Profiles & Dimensions**

\*The profiles shown are standard dimensions. Crisp can supply any custom profile\*

