



• Installation Details

Refer to the Crisp handling and installation guide for in-depth instructions.

Please add an overage of 12-15%. This allows for greater flexibility during the evaluation process on-site to ensure the best outcome.

Crisp Pine can be installed vertically or horizontally

• Finish Specifications

All products are factory-finished and arrive on-site ready for installation

• Pre-finish: Crisp Pine features a two-coat system.

- First conditioning, clear coat is applied to front face, back and two edges.

- The second is a color coat that is applied to the front-finished face.

• Applied Finish: Broda Clarity Acrylic, Water-borne, low V.O.C, film-building finish.

• Color: Broda Clarity 214 Teak

• Coating Options:

- Broda Clarity acrylic clear top coat, available in gloss, satin or flat finish.

• Species

Pine (SPF spruce-pine-fir) is a versatile and sustainable option for wood cladding projects. Renowned for its natural beauty, strength, and adaptability, pine is a popular choice among architects and designers. With its distinct grain pattern and warm color, pine adds a touch of elegance to any space. Whether stained or left natural, pine complements various architectural styles, making it a timeless and versatile option for any space.

• Wood Grade

Crisp Pine is available in:

- C&BTR Clear Select 6'-16' even lengths, available in specified tally.

- Elite (Premium #2) 6'-16' even lengths, available in specified tally.

Product pictures of Pine on crisp wood co website features Elite (Premium #2) unless noted

• Moisture Content

Crisp Pine is kiln-dried to a MC of 12-15%. This may fluctuate during transportation or warehousing.

Make sure to acclimatize on-site before installation.

• Surface and Texture

Crisp Pine smooth is pre-sanded to a smooth finish.

• Profiles & Dimensions

*The profiles shown are standard dimensions.

Crisp can supply any custom profile*

