



• Installation Details

Refer to the Crisp handling and installation guide for in-depth instructions.

Please add an overage of 12-15%. This allows for greater flexibility during the evaluation process on-site to ensure the best outcome.

Crisp WRC can be installed vertically or horizontally

• Finish Specifications

All products are factory-finished and arrive on-site ready for installation

• Pre-finish: Crisp WRC features a two-coat system.

- First coat applied to front face, back and two edges.
- Second coat applied to front finished face.

- Ends must be sealed on site prior to installation.

• Applied Finish: Broda SLT or Broda DR. Water-borne, natural oil, low V.O.C, alkyd, penetrating stain.

• Color: Broda 336 Barnboard

• Coating Options:

- Broda clear U.V. top coat oil for exterior.
- Broda Clarity acrylic clear top coat for interior.

• Species

Western Red Cedar is a medium - to large-sized, evergreen, scale-leaved conifer. It is one of the most valuable conifers owing to the unique colour, texture, and durability of its wood.

It is renewable, biodegradable, sourced from sustainably managed forests, naturally resistant to rot and decay, and is one of the most dimensionally stable softwoods.

• Wood Grade

Crisp WRC is available in:

- Select tight knot specified lengths
- C&BTR clear mixed grain 6'-20' random tally
- C&BTR clear vertical grain 3'-20' random tally

Product pictures of WRC on crisp wood co website features select tight knot unless noted

• Fire Rating

Class B flame spread

• Moisture Content

Crisp Western Red Cedar is kiln-dried to a MC of 12-15%. This may fluctuate during transportation or warehousing. Make sure to acclimatize on-site before installation.

• Surface and Texture

Crisp WRC Resawn has a rough texture with vertical band saw marks.

• Profiles & Dimmensions

The profiles shown are standard dimensions. Crisp can supply any custom profile

