CRISP **WOOD**co.

PRODUCT DATA SHEET · 3D CLADDING

Lunawood Triple

Lunawood thermally modified Nordic spruce in the Luna Triple tongue and groove profile, for three-dimensional cladding.

Specification

Species	Lunawood thermally modified Nordic spruce
Grade	Select tight knot (STK)
Texture	Smooth
Profile	Luna Triple tongue and groove
Lengths	6 to 16 ft, specific lengths available
Applications	Exterior and interior cladding, exterior soffits and ceilings
Coating	Premium waterborne multi-coat system, factory applied, sealed on all four sides
Colours	Strom, Driv, Natt, Arctic (4)

Characteristics

- **Heat and steam only.** Thermally modified with heat and steam, with no chemicals added.
- **Stable and durable.** The process improves dimensional stability and durability through the whole board.
- **Responsibly sourced.** Slow-grown Northern softwood from Finnish forests.

Supply

- Delivered complete, sealed on all four sides and ready to install.
- Lead time is approximately two weeks from date of confirmation.
- Every order ships with one gallon of matched touch-up.
- Custom orders in other species, profiles and sizes are also available.

Installation

- Install to the Crisp Wood Co. Installation Manual, over a weather barrier on furring strips (ventilated rainscreen).
- Stainless steel fasteners. Nails to penetrate at least 1.25 in into solid wood.
- Seal all field cuts before installation.
- Also follow the Lunawood installation guides; where they differ, the stricter requirement governs.

Warranty and care

15-year limited warranty, kept in effect by the Crisp maintenance program: wash every year; re-seal siding, soffits, fascia and trim every five years with a Crisp-approved sealer; keep records. Full terms at crispwoodco.com/warranty.

Samples and support

Samples are free for architects and designers. Guide specification text, documents and consultation booking: crispwoodco.com/for-architects