CRISP **WOOD**co.

PRODUCT DATA SHEET

Western Red Cedar

Western Red Cedar in three grades and three profiles, sealed on all four sides, for exterior cladding, soffits and interior walls.

Specification

Species	Western Red Cedar
Grade	Select tight knot (STK), Clear mixed grain, Clear vertical grain
Texture	Smooth
Profiles	1/8 in gap fine line, S4S (smooth four sides), V-groove
Sizes	1×3, 1×4, 1×5, 1×6, 1×8, 1×10, 2×2, 2×4, 2×6, 2×8, 2×10, 2×12
Lengths	6 to 20 ft, specific lengths available
Applications	Exterior and interior cladding, exterior soffits and ceilings
Coating	Premium waterborne multi-coat system, factory applied, sealed on all four sides
Colours	Halo, Ashen, Cove, Forma, Slate, Corten, Cinder, Carbon (8)

Characteristics

- **Naturally durable.** Natural extractives in the heartwood help it resist decay and insects.
- **Stays true.** Among the most stable softwoods, resisting warping, twisting and checking.
- **Light and insulating.** One of the lightest commercial softwoods, with natural thermal and acoustic insulating value.

Supply

- Delivered complete, sealed on all four sides and ready to install.
- Lead time is approximately two weeks from date of confirmation.
- Every order ships with one gallon of matched touch-up.
- Custom orders in other species, profiles and sizes are also available.

Installation

- Install to the Crisp Wood Co. Installation Manual, over a weather barrier on furring strips (ventilated rainscreen).
- Stainless steel fasteners. Nails to penetrate at least 1.25 in into solid wood.
- Seal all field cuts before installation.

Warranty and care

15-year limited warranty, kept in effect by the Crisp maintenance program: wash every year; re-seal siding, soffits, fascia and trim every five years with a Crisp-approved sealer; keep records. Full terms at crispwoodco.com/warranty.

Samples and support

Samples are free for architects and designers. Guide specification text, documents and consultation booking: crispwoodco.com/for-architects